


$\textbf{Tender specification} - \textbf{Trampoline XL - flashtramp}^{\texttt{®}} \textbf{- Pirate}$

Trampoline XL - flashtramp® - Pirate

Art. No. 7250081









Technical Data

Lighting units 4 pieces inclusive

Our recommendation 4x Red

Unit space area 1.75 x 2.25 m

Jumping area $1.25 \times 1.75 \text{ m} (= 2.19 \text{ m}^2)$

Safety space area 5.25 x 5.75 m Height of unit 0.00 m Max. free drop height 0.90 m

Age range 3+ Numbers of users 4

Heaviest component 250 kg
Total weight 250 kg
Assembly time 1.00 hour
Installers 2 persons
Foundations none

If you have any questions, we'd be happy to help:



TENDER SPECIFICATION TRAMPOLINE XL - FLASHTRAMP® - PIRATE

Tender specification

Jumping device in a rectangular design – Unit space area 1.75 x 2.25 m, jumping area 1.25 x 1.75 m (2.19 m²). Frame made of durable, hot-dip galvanized steel construction.

Closed jumping surface with 'Pirate' motif, made of dyed through polyamide wing lamellas with conical seat joints to reduce the load on the steel wire ropes and with nubby GRIPTEQ® surface for optimal grip in all directions of movement.

flashtramp® – enlighten your creativity

Including 4 flashtramp[®]-lighting units (4 x Red) consisting of an encapsulated generator and two high-performance LEDs, which use micro-energy harvesting to convert the jump energy into light impulses.

WEEE-certified: reg. no. DE 60731611

Rim with shock-absorbing fall protection plates. Including 62 highly robust DURAPTEQ® screw plate tension springs with noise-reducing plain bearing sleeves.

Installation depth: 0.45 m, at ground level.

Foundations are not required - the jumping device is completely assembled at the factory and delivered ready for installation. Maintenance and cleaning of the interior can be done quickly and easily via the jump mat. Hook notches on the DURAPTEQ® springs make work easier. Installation and operating costs are minimized!

Selectable colors:

Fall protection rim - in the standard colors Black, Moss green, Reddish brown. Special colors available on request.