


Tender specification — Trampoline S - flashtramp® - Skull

Trampoline S - flashtramp® - Skull

Art. No. 7250043



tuev-sued.de/ps-zert



flashtramp[®] enlighten your creativity

Technical Data

Lighting units 4 pieces inclusive

Our recommendation 4x Red

Unit space area 1.25 x 1.25 m

Jumping area $0.75 \times 0.75 \text{ m} (= 0.56 \text{ m}^2)$

Safety space area 3.75 x 3.75 m Height of unit 0.00 m Max. free drop height 0.90 m

Age range 3+ Numbers of users 1

Heaviest component 130 kg
Total weight 130 kg
Assembly time 1.00 hour
Installers 2 persons
Foundations none

If you have any questions, we'd be happy to help:

smb Seilspielgeräte GmbH Berlin in Hoppegarten Technikerstraße 6/8 DE-15366 Hoppegarten Fon. +49 (0) 3342 50837-20 Fax. +49 (0) 3342 50837-80 info@smb.berlin www.smb.berlin



TENDER SPECIFICATION TRAMPOLINE S - FLASHTRAMP® - SKULL

Tender specification

Jumping device in a square design – Unit space area $1.25 \times 1.25 \text{ m}$, jumping area $0.75 \times 0.75 \text{ m}$ (0.56 m^2). Frame made of durable, hot-dip galvanized steel construction.

Closed jumping surface with 'Skull' motif, made of dyed through polyamide wing lamellas with conical seat joints to reduce the load on the steel wire ropes and with nubby GRIPTEQ® surface for optimal grip in all directions of movement.

flashtramp® – enlighten your creativity

Including 4 flashtramp[®]-lighting units (4 x Red) consisting of an encapsulated generator and two high-performance LEDs, which use micro-energy harvesting to convert the jump energy into light impulses.

WEEE-certified: reg. no. DE 60731611

Rim with shock-absorbing fall protection plates. Including 32 highly robust DURAPTEQ® screw plate tension springs with noise-reducing plain bearing sleeves.

Installation depth: 0.45 m, at ground level.

Foundations are not required - the jumping device is completely assembled at the factory and delivered ready for installation. Maintenance and cleaning of the interior can be done quickly and easily via the jump mat. Hook notches on the DURAPTEQ® springs make work easier. Installation and operating costs are minimized!

Selectable colors:

Fall protection rim - in the standard colors Black, Moss green, Reddish brown. Special colors available on request.