

Tender specification – Trampoline combination – modutramp® - big rallye

 $\label{eq:trampoline} \textbf{Trampoline combination} - \textbf{modutramp}^{\text{@}} \textbf{ - big rallye}$

Art. No. 7235001



tuev-sued.de/ps-zert



reddot design award honourable mention 2012



Technical data

Unit space area $11.60 \times 6.35 \text{ m}$ Jumping area 16.61 m^2 Safety space area $15.75 \times 10.52 \text{ m}$

Height of unit 0.00 m Max. free drop height 0.90 m

Age range 3+ Number of users 22

Heaviest component 230 kg
Total weight 3960 kg
Assembly time 16.00 hours
Installers 2-3 persons
Foundations none

If you have any questions, we'd be happy to help:



TENDER SPECIFICATION TRAMPOLINE COMBINATION - MODUTRAMP® - BIG RALLYE

Tender specification

Jumping device combination - unit space area 11.60 x 6.35 m, jumping area in total 16.61 m².

consisting of:

11 x modutramp® switch

Jumping devices in a square design – single unit space area $1.25 \times 1.25 \text{ m}$, single jumping area 0.53 m^2 . Frame made of durable, hot-dip galvanized steel construction.

Closed jumping surface, made of dyed through polyamide wing lamellas with conical seat joints to reduce the load on the steel wire ropes and with nubby GRIPTEQ® surface for optimal grip in all directions of movement.

Rim with shock-absorbing fall protection plates. Including 352 highly robust DURAPTEQ® screw plate tension springs with noise-reducing plain bearing sleeves.

Installation depth: 0.45 m, at ground level.

11x modutramp[®] 90

Jumping devices describe an angle of 90 degrees - single unit space area 1.85 x 1.85 m, single effective jumping area 0.98 m². Frame made of durable, hot-dip galvanized steel construction.

Closed jumping surface, made of dyed through polyamide wing lamellas with conical seat joints to reduce the load on the steel wire ropes and with nubby GRIPTEQ® surface for optimal grip in all directions of movement.

Rim with shock-absorbing fall protection plates. Including 440 highly robust DURAPTEQ® screw plate tension springs with noise-reducing plain bearing sleeves.

Installation depth: 0.45 m, at ground level.

Foundations are not required - the jumping device is completely assembled at the factory and delivered ready for installation.

Maintenance and cleaning of the interior can be done quickly and easily via the jump mat. Hook notches on the DURAPTEQ® springs make work easier. Installation and operating costs are minimized!

Selectable colors:

Fall protection rim - in the standard colors Black, Moss green, Reddish brown. Special colors available on request.

Jump mat - available in the standard colors Persidion black, Borneo green, Alpaca gray, Pearl blackberry, Bengal red, Jakarta orange, Mocha brown, Bali yellow, Lapis blue and Sand beige. Individual colors available on request.